

CLAIMS

1. A method for estimating a value of a diffusion tensor, said method comprising:

obtaining, from a plurality of test subjects, DT-MRI data from which an initial estimate of the tensor can be derived;

determining a first value indicative of intra-subject variations in said data;

determining a second value indicative of inter-subject variation in said data; and

at least in part on the basis of said first and second values, determining a subject-specific additive offset for adjusting said DT-MRI data.
2. The method of claim 1, further comprising generating adjusted data by adjusting said DT-MRI data by said offset.
3. The method of claim 2, further comprising generating a bowtie plot from said adjusted data.
4. The method of claim 1, further comprising selecting said DT-MRI data to represent an initial estimate of said diffusion tensor value.
5. The method of claim 1, further comprising selecting said DT-MRI data to represent echo data from which an initial estimate of the diffusion tensor can be derived.
6. The method of claim 1, wherein determining a first value comprises determining an average intra-subject variance.
7. The method of claim 1, wherein determining a second value comprises determining an inter-subject variance.
8. A computer-readable medium having encoded thereon software for estimating a value of a diffusion tensor, said software comprising instructions for:

obtaining, from a plurality of test subjects, DT-MRI data from which an initial estimate of the tensor can be derived;

determining a first value indicative of intra-subject variations in said data;

determining a second value indicative of inter-subject variation in said data; and

at least in part on the basis of said first and second values, determining a subject-specific additive offset for adjusting said DT-MRI data.

9. The computer-readable medium of claim 8, wherein the software further comprises instructions for generating adjusted data by adjusting said DT-MRI data by said offset.
10. The computer-readable medium of claim 9, wherein the software further comprises instructions for generating a bowtie plot from said adjusted data.
11. The computer-readable medium of claim 8, wherein the software further comprises instructions for selecting said DT-MRI data to represent an initial estimate of said diffusion tensor value.
12. The computer-readable medium of claim 8, wherein the software further comprises instructions for selecting said DT-MRI data to represent echo data from which an initial estimate of the diffusion tensor can be derived.
13. The computer-readable medium of claim 8, wherein the instructions for determining a first value comprise instructions for determining an average intra-subject variance.
14. The computer-readable medium of claim 8, wherein the instructions for determining a second value comprise instructions for determining an inter-subject variance.
15. A system for estimating a value of a diffusion tensor, said system comprising:
 - an MRI machine;
 - a processor in data communication with the MRI machine;

a computer-readable medium in data communication with the processor, the
computer-readable medium having encoded thereon software as recited in
claim 9.